



PZ

road cleaner with nozzles

TECHNICAL DATA

- capacity 8-10 m³, one section tank
- waterpump VOGELSANG 136-140 QD
- outlet opening with 3-hole flange connection
- each washer controlled separately by an electro-valve
- front sprinkler bar, controlled left/right
- additional water pump with capacity 30 dm³/min by pressure 150BAR
- automatic reel with pressure hose with length of 15 meter



STANDARD EQUIPMENT:

- ✓ the water tank made of black steel,
- ✓ the rear part of tank with compartment for water pumps,
- ✓ water pump VOGELSANG 136-140QD,
- ✓ additional water pump with reel with pressure hose 15 meter,
- ✓ inspection hatch with a diameter of 550 mm,
- ✓ tank equipped with 3 breakwaters/2 longitudinal + 1 transverse,
- ✓ indicators on both sides of the tank and percentage indicator of water level, displayed on the monitor with diameter of min 4" located in the driver's cab,
- ✓ water tank with connection for filling directly from the hydrant,
- ✓ connection with a DN52 firefighter type connector, firefighter hose for filling the tank,
- ✓ the ability to pump water to sweepers,
- ✓ sprinkler washing strip mounted in the interchangeable system on the faceplate,
- ✓ strip equipped with min: 3 scrubbers adjustable in two planes enabling washing of streets in the front of vehicle, washing bar, with adjustment - right/left; up/down,
- ✓ spray washing bar with a min 10 spray nozzles covering a washing width of approx. 3 meter
- ✓ rear fog sprinkler bar - optional,
- ✓ control panel mounted in the driver's cab, allowing individual washers to be switch on/off
- ✓ switching on/off the sprinkler bar, controlling the pressure of the waterjet, switching on the warning lights,
- ✓ hydrant key,
- ✓ aluminium troughs on the both sides of the housing.

DOBROWOLSKI

Obróńców Warszawy 26a
67-400 Wschowa, Poland

+48 65 540 36 17
mail@dobrowolski.com.pl

DOBROWOLSKI

www.dobrowolski.com.pl